



GE STAINLESS STEEL COUPLING



STYLE 77S



Style 77S Stainless Steel Coupling is designed with cross Rib construction for 2 inch and 3 inch and for other sizes they come with plain surface. Couplings are cast of high quality Type 304SS for corrosion resistance and strength. Alternatively, Couplings with SS 316 castings are also available.

MATERIAL OF CONSTRUCTION

Housing : SS 304 / SS 316

Gasket : EPDM or Nitrile

Bolts and nut : Single spanner Track head Type in Alloy Steel Zn/Cd Plated or SS 304/316.



COUPLING SIZE INCHES	PIPE OUTSIDE DIAMETER mm	COUPLING DIMENSIONS mm			BOLT DIMENSIONS		APPROX WEIGHT EACH KGS	WORKING PRESSURE BAR
		WIDTH X	HEIGHT Y	DEPTH Z	NO.	Dia x Length inch mm		
1/2	21.4	90	52	45	2	3/8 x 50.0	0.40	52
3/4	26.9	90	54	45	2	3/8 x 50.0	0.50	52
1	33.7	100	61	45	2	3/8 x 62.0	0.70	52
1 1/4	42.4	118	67	46	2	3/8 x 62.0	0.90	52
1 1/2	48.3	127	76	46	2	3/8 x 62.0	0.90	52
2	60.3	134	98	48	2	1/2 x 62.0	1.40	52
2 1/2	73.0	161	108	46	2	1/2 x 62.0	1.35	52
2 1/2	76.2	162	110	48	2	1/2 x 62.0	1.40	52
3	88.9	167	130	48	2	1/2 x 70.0	1.90	52
4	114.3	215	153	51	2	1/2 x 70.0	2.60	52
5	141.3	245	186	51	2	5/8 x 83.0	4.10	52
6	168.3	275	225	51	2	5/8 x 83.0	5.00	52
8	219.1	355	266	61	2	3/4 x 114.3	7.50	35
10	273.0	420	340	74	2	1 x 152.0	12.0	35
12	323.9	478	390	73	2	1 x 165.0	12.00	35
14	355.6	503	420	73	2	1 x 165.0	19.00	15
16	406.4	560	480	73	4	1 x 140.0	21.00	15

13/385/08