

nmc

ZUT PUT COUPLING

FOR PLAIN END PIPING SYSTEM FOR HDPE PIPE

Completely mechanical-provides easy access throughout the system.

Best assembly-housings bolt metal-to-metal with four track-head bolts (no torque wrenches required).

Rugged, positive joint-integral teeth provide positive grip around entire pipe circumference.

Leak-tight-proven pressure-responsive gasket.


Versatile and easy-no awkward and expensive fusing equipment required.

Reliable-proven through lengthy field testing.

Strength and quality-housings cast of durable malleable or ductile iron. Available in wide Range 25-500 mm.

MATERIAL SPECIFICATION

HOUSING :	SG Ductile Iron	BS EN 1563:1997	IS 1865:2000
	or Malleable Cast Iron	BS EN 1562	IS 14329:2000
RUBBER RING :	Nitrile / EPDM		
BOLT & NUT :	BS 970 : En8 Duly heat-treated & Galvanised		



PIPE O.D. mm	DIMENSIONS approx - mm			BOLT 0 X lg. (inch x mm)	APPROX. Wt (kg.)
	X	Y	Z		
25	50	85	78	3/8 x 50	0.9
32	60	93	84	3/8 x 50	1.0
40	65	106	88	3/8 x 50	1.2
50	80	115	88	3/8 x 70	1.40
63	100	115	92	3/8 x 70	2.0
75	110	137	105	3/8 x 70	2.6
90	120	173.5	116	1/2 x 70	3.0
110	137	183	128	1/2 x 90	4.0
140	169	237	142	5/8 x 90	6.8
160	192	254	148	5/8 x 90	7.6
180	210	270	151	5/8 x 115	8.9
200	250	310	153	5/8 x 115	10.0
225	270	340	154	3/4 x 127	13.0
250	300	376	162	3/4 x 127	18.0
280	315	402	170	3/4 x 127	18.0
315	356	432	178	7/8 x 127	21.0
355	413	478	195	1 x 178	37.0
400	465	564	229	1 x 178	46.0
450	516	614	241	1 x 178	58.0
500	566	665	254	1 X 178	65.0

13/15/08

Nanda Millar Company

Office : 32A, Chittaranjan Avenue, 2nd Floor, Kolkata-700 012. India. Tel : +91 33 2212 3530 / 3531 / 1783

Fax : +91 33 2212 2070. E-mail : nmc@nandagroup.com, nmcjp@hotmail.com. URL : www.nandagroup.com



An ISO 9001 : 2000
Registered Company